

ANNEX TO THE CPM REPORT

List of the ITU-R Recommendations related to the CPM Report to WRC-03

Chapter 1 - Radionavigation, radionavigation-satellite and radiolocation services		
Recommendation ITU-R P.452-9	Prediction procedure for the evaluation of microwave interference between stations on the surface of the Earth at frequencies above about 0.7 GHz	Volume 2000 Series P, Part 2
Recommendation ITU-R S.465-5	Reference earth-station radiation pattern for use in coordination and interference assessment in the frequency range from 2 to about 30 GHz	Volume 2000 Series S, Part 1
Recommendation ITU-R SA.510-2	Feasibility of frequency sharing between the space research service and other services in bands near 14 and 15 GHz - Potential interference from data relay satellite systems	Volume 2000 Series SA
Recommendation ITU-R S.524-7	Maximum permissible levels of off-axis e.i.r.p. density from earth stations in GSO network operating in the fixed-satellite service transmitting in the 6, 14 and 30 GHz frequency bands	Supplement 1 Volume 2000 Series S, Parts 1, 2 and 3
Recommendation ITU-R P.526-6	Propagation by diffraction	Volume 2000 Series P, Part 1
Recommendation ITU-R S.580-5	Radiation diagrams for use as design objectives for antennas of earth stations operating with geostationary satellites	Volume 2000 Series S, Part 1
Recommendation ITU-R S.728-1	Maximum permissible level of off-axis e.i.r.p. density from very small aperture terminals (VSATs)	Volume 2000 Series S, Part 1
DRR ITU-R RA.769-1	Protection criteria used for radioastronomical measurements	Doc. 7/53
Recommendation ITU-R SA.1018	Hypothetical reference system for systems comprising data relay satellites in the geostationary orbit and user spacecraft in low Earth-orbits	Volume 2000 Series SA
Recommendation ITU-R S.1068	Fixed-satellite and radiolocation/radionavigation services sharing in the band 13.75 to 14 GHz	Volume 2000 Series S, Part 3
Recommendation ITU-R S.1069	Compatibility between the fixed-satellite service and the space science services in the band 13.75-14 GHz	Volume 2000 Series S, Part 3
Recommendation ITU-R SA.1071	Use of the 13.75 to 14.0 GHz band by the space science services and the fixed satellite service	Volume 2000 Series SA
Recommendation ITU-R M.1088	Considerations for sharing with systems of other services operating in the bands allocated to the radionavigation-satellite service	Volume 2000 Series M, Part 5
Recommendation ITU-R SA.1155	Protection criteria related to the operation of data relay satellite systems	Volume 2000 Series SA
Recommendation ITU-R M.1227-2	Technical and operational characteristics of wind profiler radars in bands in the vicinity of 1 000 MHz	Volume 2000 Series M, Part 4
Recommendation ITU-R M.1313-1	Technical characteristics of maritime radionavigation radars	Volume 2000 Series M, Part 4

Recommendation ITU-R M.1317	Considerations for sharing between systems of other services operating in bands allocated to the radionavigation-satellite and aeronautical radionavigation services and the global navigation satellite system (GLONASS-M)	Volume 2000 Series M, Part 5
Recommendation ITU-R S.1342	Method for determining coordination distances, in the 5 GHz band, between the international standard Microwave Landing System stations operating in the ARNS and non-geostationary MSS stations providing feeder uplink services	Volume 2000 Series S, Part 3
DRR ITU-R M.1372	Efficient use of the radio spectrum by radar stations in the radiodetermination service	Doc. 8/101
Recommendation ITU-R SA.1414	Characteristics of data relay satellite systems	Volume 2000 Series SA
Recommendation ITU-R S.1428-1	Reference FSS earth-station radiation patterns for use in interference assessment involving non-GSO satellites in frequency bands between 10.7 GHz and 30 GHz	Volume 2000 Series S, Part 1
Recommendation ITU-R M.1460	Technical and operational characteristics and protection criteria of radiodetermination and meteorological radars in the 2 900-3 100 MHz band	Volume 2000 Series M, Part 4
DRR ITU-R M.1461	Procedures for determining the potential for interference between radars operating in the radiodetermination service and systems in other services	Doc. 8/100
Recommendation ITU-R M.1463	Characteristics of and protection criteria for radars operating in the radiodetermination service in the frequency band 1 215-1 400 MHz	Volume 2000 Series M, Part 4
DRR ITU-R M.1464	Characteristics of and protection criteria for radionavigation and meteorological radars operating in the frequency band 2 700-2 900 MHz	Doc. 8/97
Recommendation ITU-R M.1477	Technical and performance characteristics of current and planned radionavigation-satellite service (space-to-Earth) and aeronautical radionavigation service receivers to be considered in interference studies in the band 1 559-1 610 MHz	Volume 2000 Series M, Part 5
DRR ITU-R RA.1513	Levels of data loss to radio astronomy observations and percentage-of-time criteria resulting from degradation by interference for frequency bands allocated to the radio astronomy on a primary basis	Doc. 7/51
Recommendation ITU-R M.1583	Interference calculations between non-GSO MSS or RNSS satellite systems and radio astronomy telescope sites	ITU Web (Doc. 8/BL/16)
DNR ITU-R M.[RAD.CHARZ]	Technical and operational characteristics, and criteria for protecting the mission of radars in the radiolocation and radionavigation service operating in the frequency band 13.75-14 GHz	Doc. 8/98
DNR ITU-R M.[RNSS1]	Protection criterion for the aeronautical radionavigation service with respect to aggregate emissions from space stations in the radionavigation-satellite service in the band 1 164-1 215 MHz	Doc. 8/77
DNR ITU-R M.[RNSS2]	Methodology for assessing the aggregate epfd from all RNSS satellites of all RNSS systems operating in the 1 164-1 215 MHz band.	Doc. 8/128

Chapter 2 - Mobile, mobile-satellite and space science services		
Recommendation ITU-R SA.363-5	Space operation systems. Frequencies, bandwidths and protection criteria	Volume 2000 Series SA
Recommendation ITU-R SA.364-5	Preferred frequencies and bandwidths for manned and unmanned near-Earth research satellites	Volume 2000 Series SA
Recommendation ITU-R SA.509-2	Generalized space research Earth station and radio astronomy antenna radiation pattern for use in interference calculations, including coordination procedures	Volume 2000 Series SA
Recommendation ITU-R SA.510-2	Feasibility of frequency sharing between the space research service and other services in bands near 14 and 15 GHz - Potential interference from data relay satellite systems	Volume 2000 Series SA
Recommendation ITU-R SA.577-5	Preferred frequencies and necessary bandwidths for spaceborne active remote sensors	Volume 2000 Series SA
Recommendation ITU-R SA.609-1	Protection criteria for telecommunication links for manned and unmanned near-Earth research satellites	Volume 2000 Series SA
DRR ITU-R RA.611-2	Protection of the radio astronomy service from spurious emissions	Doc. 7/71
Recommendation ITU-R S.672-4	Satellite antenna radiation pattern for use as a design objective in the fixed-satellite service employing geostationary satellites	Volume 2000 Series S, Part 3
Recommendation ITU-R S.728-1	Maximum permissible level of off-axis e.i.r.p. density from very small aperture terminals (VSATs)	Volume 2000 Series S, Part 1
DRR ITU-R F.758-2	Considerations in the development of criteria for sharing between the terrestrial fixed service and other services	Doc. 9/BL/51
DRR ITU-R RA.769-1	Protection criteria used for radioastronomical measurements	Doc. 7/53
Recommendation ITU-R SA.1014	Telecommunication requirements for manned and unmanned deep-space research	Volume 2000 Series SA
Recommendation ITU-R SA.1016	Sharing considerations relating to deep-space research	Volume 2000 Series SA
Recommendation ITU-R SA.1017	Preferred method for calculating link performance in the space research service	Volume 2000 Series SA
Recommendation ITU-R SA.1024-1	Necessary bandwidths and preferred frequency bands for data transmission from Earth exploration satellites (not including meteorological satellites)	Volume 2000 Series SA
DRR ITU-R SA.1029-1	Interference criteria for satellite passive remote sensing	Doc. 7/50
DRR ITU-R M.1036-1	Spectrum considerations for implementation of International Mobile Telecommunications-2000 (IMT-2000) in the bands 1 885-2 025 MHz and 2 110-2 200 MHz	Doc. 8/112
Recommendation ITU-R M.1039-2	Co-frequency sharing between stations in the mobile service below 1 GHz and mobile earth stations of non-geostationary mobile-satellite systems (Earth-to-space) using FDMA	Volume 2000 Series M, Part 5
DRR ITU-R M.1042-1	Disaster communications in the amateur and amateur-satellite services	Doc. 8/89

Recommendation ITU-R F.1094-1	Maximum allowable error performance and availability degradations to digital radio-relay systems arising from interference from emissions and radiations from other sources	Volume 2000 Series F, Part 1A
Recommendation ITU-R F.1105	Transportable fixed radiocommunications equipment for relief operations	Volume 2000 Series F, Part 1B
Recommendation ITU-R F.1108-3	Determination of the criteria to protect fixed service receivers from the emissions of space stations operating in non-geostationary orbits in shared frequency bands	ITU Web (Doc. 9/BL/36)
Recommendation ITU-R M.1141-1	Sharing in the 1-3 GHz frequency range between non-geostationary space stations operating in the mobile-satellite service and stations in the fixed service	Volume 2000 Series M, Part 5
Recommendation ITU-R M.1142-1	Sharing in the 1-3 GHz frequency range between geostationary space stations operating in the mobile-satellite service and stations in the fixed service	Volume 2000 Series M, Part 5
Recommendation ITU-R S.1151	Sharing between the inter-satellite service involving geostationary satellites in the fixed-satellite service and the radionavigation service at 33 GHz	Volume 2000 Series S, Part 3
Recommendation ITU-R SA.1155	Protection criteria related to the operation of data relay satellite systems	Volume 2000 Series SA
Recommendation ITU-R SA.1157	Protection criteria for deep-space research	Volume 2000 Series SA
DRR ITU-R SA.1158-2	Sharing of the 1 675-1 710 MHz band between the meteorological-satellite service (space-to-Earth) and the mobile-satellite service (Earth-to-space)	Doc. 7/77
Recommendation ITU-R SA.1166-2	Performance and interference criteria for active spaceborne sensors	Volume 2000 Series SA
Recommendation ITU-R M.1174-1	Characteristics of equipment used for on-board communications in the bands between 450 and 470 MHz	Volume 2000 Series M, Part 3
DRR ITU-R M.1184-1	Technical characteristics of mobile satellite systems in the frequency bands below 3 GHz for use in developing criteria for sharing between the mobile-satellite service (MSS) and other services	Doc. 8/111
Recommendation ITU-R F.1242	Radio-frequency channel arrangements for digital radio systems operating in the range 1 350 MHz to 1 530 MHz	Volume 2000 Series F, Part 1A
Recommendation ITU-R F.1245-1	Mathematical model of average radiation patterns for line-of-sight point-to-point radio-relay system antennas for use in certain coordination studies and interference assessment in the frequency range from 1 to about 70 GHz	Volume 2000 Series F, Part 2
DRR ITU-R SA.1260	Feasibility of sharing between active spaceborne sensors and other services in the range 420-470 MHz	Doc. 7/69
DRR ITU-R SA.1264	Frequency sharing between the meteorological aids service and the mobile-satellite service (Earth-to-space) in the 1 675-1 700 MHz band	Doc. 7/68
Recommendation ITU-R SA.1280	Selection of active spaceborne sensor emission characteristics to mitigate the potential for interference to terrestrial radars operating in frequency bands 1-10 GHz	Volume 2000 Series SA
Recommendation ITU-R M.1313-1	Technical characteristics of maritime radionavigation radars	Volume 2000 Series M, Part 4

DRR ITU-R F.1336-1	Reference radiation patterns of omnidirectional and other antennas in point-to-multipoint systems for use in sharing studies	Doc. 9D/212, Annex 6
Recommendation ITU-R SA.1344	Preferred frequency bands and bandwidths for the transmission of space VLBI data	Volume 2000 Series SA
DRR ITU-R M.1372	Efficient use of the radio spectrum by radar stations in the radiodetermination service	Doc. 8/101
Recommendation ITU-R M.1390	Methodology for the calculation of IMT-2000 terrestrial spectrum requirements	Volume 2000 Series M, Part 2
Recommendation ITU-R SA.1396	Protection criteria for the space research service in the 37-38 and 40-40.5 GHz bands	Volume 2000 Series SA
Recommendation ITU-R F.1399-1	Vocabulary of terms for wireless access	Doc. 9/BL/5
Recommendation ITU-R F.1400	Performance and availability requirements and objectives for fixed wireless access to public switched telephone network	Volume 2000 Series F, Part 1B
Recommendation ITU-R F.1401	Frequency bands for fixed wireless access systems and the identification methodology	Volume 2000 Series F, Part 1B
Recommendation ITU-R SA.1414	Characteristics of data relay satellite systems	Volume 2000 Series SA
Recommendation ITU-R S.1426	Aggregate power flux-density limits, at the FSS satellite orbit for radio local area network (RLAN) transmitters operating in the 5 150-5 250 MHz band sharing frequencies with the FSS (RR No. S5.447A)	Volume 2000 Series S, Part 2
Recommendation ITU-R S.1427	Methodology and criterion to assess interference from radio local area (RLAN) transmitters to non-GSO MSS feeder links in the band 5 150-5 250 MHz	Volume 2000 Series S, Part 3
Recommendation ITU-R SM.1448	Determination of the coordination area around an earth station in the frequency bands between 100 MHz and 105 GHz	Volume 2000 Series SM, Part 2
DRR ITU-R M.1450-1	Characteristics of broadband radio local area networks (RLANS)	Doc. 8/96
Recommendation ITU-R M.1454	E.i.r.p. density limit and operational restrictions for RLANS1 or other wireless access transmitters in order to ensure the protection of feeder links of non-geostationary systems in the mobile-satellite service in the frequency band 5 150-5 250 MHz	Volume 2000 Series M, Part 1
Recommendation ITU-R M.1456	Minimum performance characteristics and operational conditions for high altitude platform stations providing IMT-2000 in the bands 1 885-1 980 MHz, 2 010-2 025 MHz and 2 110-2 170 MHz in Regions 1 and 3 and 1 885-1 980 MHz and 2 110-2 160 MHz in Region 2	Volume 2000 Series M, Part 2
Recommendation ITU-R M.1459	Protection criteria for telemetry systems in the aeronautical mobile service and mitigation techniques to facilitate sharing with geostationary broadcasting-satellite and mobile-satellite services in the frequency bands 1 452-1 525 MHz and 2 310-2 360 MHz	Volume 2000 Series M, Part 3
DRR ITU-R M.1461	Procedures for determining the potential for interference between radars operating in the radiodetermination service and systems in other services	Doc. 8/100
Recommendation ITU-R M.1462	Characteristics of and protection criteria for radars operating in the radiolocation service in the frequency band 420-450 MHz	Volume 2000 Series M, Part 4

Recommendation ITU-R M.1480	Essential technical requirements of mobile Earth stations of geostationary mobile-satellite systems that are implementing the GMPCS-Memorandum of Understanding arrangements in parts of the frequency band 1-3 GHz	Volume 2000 Series M, Part 5
Recommendation ITU-R F.1490	Generic requirements for fixed wireless access (FWA) systems	Volume 2000 Series F, Part 1B
Recommendation ITU-R F.1499	Radio transmission systems for fixed broadband wireless access (BWA) based on cable modem standards	Volume 2000 Series F, Part 1B
DRR ITU-R RA.1513	Levels of data loss to radio astronomy observations and percentage-of-time criteria resulting from degradation by interference for frequency bands allocated to the radio astronomy on a primary basis	Doc. 7/51
Recommendation ITU-R M.1583	Interference calculations between non-GSO MSS or RNSS satellite systems and radio astronomy telescope sites	ITU Web (Doc. 8/BL/16)
Recommendation ITU-R F.1567	Radio-frequency channel arrangement for digital fixed wireless systems operating in the frequency band 406.1 to 450 MHz	ITU Web (Doc. 9/BL/23)
DNR ITU-R M.[DR.RCIRC]	Global cross-border circulation of radiocommunication equipment in emergency and disaster relief situations	Doc. 8/73
DNR ITU-R M.[8B-CHAR]	Characteristics of and protection criteria for radiolocation, aeronautical radionavigation and meteorological radars operating in the frequency bands between 5 250 and 5 850 MHz	Doc. 8/74 + Corr.1
DNR ITU-R F.[FWA5GHz- EESS]	Operational and deployment requirements for fixed wireless access (FWA) systems in Region 3 to ensure the protection of systems in the EESS (active) in the band 5 250-5 350 MHz	Doc. 9/BL/46
DNR ITU-R SA.[Doc. 7/46]	Sharing in the band 5 250-5 350 MHz between the Earth exploration-satellite service (active) and wireless access systems (including RLANs) in the mobile service	Doc. 7/46
PDNR ITU-R M.[WAS5GHz- EESS]	E.i.r.p. limit and operational restrictions for wireless access systems (including RLANs) [in the mobile service] in order to ensure the protection of systems in the Earth exploration-satellite service (active) and the space research service (active) in the band 5 250-5 350 MHz	Attachment 12 to Doc. 8A-9B/132
PDNR ITU-R M.[METHOD. NWA. SPECTRUM]	Methodology for accessing the required spectrum for generic broadband NWA networks (RLANs)	Attachment 11 to Doc. 8A-9B/205
PDNR ITU-R M.[WAS5GHz EXPANSION- EESS]	Operational and deployment requirements for wireless access systems (including RLANs) [in the mobile service] to facilitate sharing between these systems and systems in the Earth exploration-satellite service (active) and the space research service (active) in the band 5 470-5 570 MHz	Attachment 11 to Doc. 8A-9B/132
PDNR ITU-R M.[8A- 9B.RLAN.DFS]	Dynamic frequency selection (DFS) in wireless access systems including RLANs to facilitate sharing between these systems and radiodetermination systems in the frequency bands [5 250-5 350] and 5 470-5 725 MHz	Attachment 10 to Doc. 8A-9B/132
DNR ITU-R M.[AMSS]	Technical and operational requirements for aircraft earth stations of aeronautical mobile-satellite service networks operating in the band 14-14.5 GHz (Earth-to-space)	Doc. 8/78
DNR ITU-R SA.[15SHAR]	Feasibility of sharing between the space research service (space-to-Earth) and the fixed and mobile services in the band 14.8-15.35 GHz	Doc. 7/58

DNR ITU-R SA.[26SHAR]	Feasibility of sharing between the space research service (space-to-Earth) and the fixed, inter-satellite, and mobile services in the band 25.5-27.0 GHz	Doc. 7/57
DNR ITU-R SA.[Doc. 7/60]	Sharing in the band 35.5-36 GHz between the Earth exploration-satellite service (active) and space research service (active), and other services allocated in this band	Doc. 7/60
DNR ITU-R M. [8B-33GHz]	Characteristics of, and protection criteria for radars operating in the radiodetermination service in the frequency band 33.4-36 GHz	Doc. 8/102
DNR ITU-R SA.[Doc. 7/62]	Sharing between command links in the space research and space operation services with the fixed, mobile and mobile-satellite services in the frequency band 257-262 MHz	Doc. 7/62
DNR ITU-R M. [IMT.HAPSINT]	A methodology for co-channel interference evaluation to determine separation distance from a system using HAPS to a cellular system to provide IMT-2000 service	Doc. 8/106
Chapter 3 - Issues concerning fixed-satellite and broadcasting-satellite services		
Recommendation ITU-R S.465-5	Reference earth-station radiation pattern for use in coordination and interference assessment in the frequency range from 2 to about 30 GHz	Volume 2000 Series S, Part 1
Recommendation ITU-R S.580-5	Radiation diagrams for use as design objectives for antennas of earth stations operating with geostationary satellites	Volume 2000 Series S, Part 1
Recommendation ITU-R P.620-4	Propagation data required for the evaluation of coordination distances in the frequency range 100 MHz to 105 GHz	Volume 2000 Series P, Part 2
Recommendation ITU-R S.673-2	Terms and definitions relating to space radiocommunications	ITU Web or Doc. 4/BL/26
Recommendation ITU-R SF.675-3	Calculation of the maximum power density (averaged over 4 kHz) of an angle-modulated carrier	Volume 2000 Series SF
Recommendation ITU-R P.681-5	Propagation data required for the design of Earth-space land mobile telecommunication systems	Supplement 1 Volume 2000 Series P, Parts 1 and 2
DRR ITU-R M.1036-1	Spectrum considerations for implementation of International Mobile Telecommunications-2000 (IMT-2000) in the bands 1 885-2 025 MHz and 2 110-2 200 MHz	Doc. 8/112
Recommendation ITU-R F.1108-3	Determination of the criteria to protect fixed service receivers from the emissions of space stations operating in non-geostationary orbits in shared frequency bands	ITU Web (Doc. 9/BL/36)
Recommendation ITU-R M.1187	A method for the calculation of the potentially affected region for a mobile-satellite service (MSS) network in the 1-3 GHz range using circular orbits	Volume 2000 Series M, Part 5
Recommendation ITU-R BO.1213	Reference receiving earth station antenna patterns for replanning purposes to be used in the revision of the WARC-77 BSS plans for Regions 1 and 3	Volume 2000 Series BO
Recommendation ITU-R M.1225	Guidelines for evaluation of radio transmission technologies for IMT-2000	Volume 2000 Series M, Part 2
Recommendation ITU-R F.1245-1	Mathematical model of average radiation patterns for line-of-sight point-to-point radio-relay system antennas for use in certain coordination studies and interference assessment in the frequency range from 1 to about 70 GHz	Volume 2000 Series F, Part 2

Recommendation ITU-R SF.1320	Maximum allowable values of power flux-density at the surface of the Earth produced by non-geostationary satellites in the fixed-satellite service used in feeder links for the mobile-satellite service and sharing the same frequency bands with radio-relay systems	Volume 2000 Series SF
Recommendation ITU-R S.1323-2	Maximum permissible levels of interference in a satellite network (GSO/FSS; non-GSO/FSS; non-GSO/MSS feeder links) in the fixed-satellite service caused by other codirectional networks below 30 GHz	ITU Web (Doc. 4/BL/32)
Recommendation ITU-R S.1325-2	Simulation methodologies for determining statistics of short-term interference between co-frequency, codirectional non-geostationary-satellite orbit (non-GSO) fixed-satellite service (FSS) networks and other non-GSO FSS or GSO FSS networks	Volume 2000 Series S, Part 2
DRR Recommendation ITU-R S.1328-4	Satellite system characteristics to be considered in frequency sharing analyses within the fixed-satellite service	ITU Web (Doc. 4/BL/36)
Recommendation ITU-R F.1336-1	Reference radiation patterns of omnidirectional, sectoral and other antennas in point-to-multipoint systems for use in sharing studies in the frequency range from 1 to about 70 GHz	Volume 2000 Series F, Part 2
DRR ITU-R SM.1413	Radiocommunication data dictionary	Doc. 1/BL/16
Recommendation ITU-R S.1428-1	Reference FSS earth-station radiation patterns for use in interference assessment involving non-GSO satellites in frequency bands between 10.7 GHz and 30 GHz	Volume 2000 Series S, Part 1
Recommendation ITU-R S.1431	Methods to enhance sharing between non-GSO FSS systems (except MSS feeder links) in the frequency bands between 10-30 GHz	Volume 2000 Series S, Part 3
Recommendation ITU-R BO.1443-1	Reference BSS earth station antenna patterns for use in interference assessment involving non-GSO satellites in frequency bands covered by RR Appendix S30	ITU Web (Doc. 6/BL/40)
Recommendation ITU-R BO.1504	Effective utilization of spectrum assigned to the broadcasting-satellite service (sound)	Supplement 1 to Volume 2000 Series BO
Recommendation ITU-R BO.1505	Coordination procedure for assignments of space operation service in the guardbands of Appendices S30 and S30A Plans of the Radio Regulations (RR)	Supplement 1 to Volume 2000 Series BO
Recommendation ITU-R S.1527	Procedure for the identification of non-geostationary-satellite orbit satellites causing interference into an operating geostationary-satellite orbit earth station	Supplement 1 to Volume 2000 Series S, Parts 1, 2 and 3
Recommendation ITU-R S.1529	Analytical method for determining the statistics of interference between non-geostationary-satellite orbit fixed-satellite service systems and other non-geostationary-satellite orbit fixed-satellite service systems or geostationary-satellite orbit fixed-satellite service networks	Supplement 1 to Volume 2000 Series S, Parts 1, 2 and 3
Recommendation ITU-R S.1554	Methodology for determining the overall accuracy of $epfd_{\downarrow}$ measurements	ITU Web (Doc. 4/BL/19)
Recommendation ITU-R S.1557	Operational requirements and characteristics of FSS systems operating in the 50/40 GHz bands for use in sharing studies between the fixed-satellite service and the fixed service	ITU Web (Doc. 4/BL/22)
Recommendation ITU-R S.1558	Methodologies for measuring $epfd_{\downarrow}$ caused by a non-geostationary-satellite orbit space station to verify compliance with operational $epfd_{\downarrow}$ limits	ITU Web (Doc. 4/BL/23)

Recommendation ITU-R S.1560	Methodology for the calculation of the worst-case interference levels from a particular type of non-geostationary fixed-satellite service system using highly-elliptical orbits into geostationary fixed-satellite service satellite networks operating in the 4/6 GHz frequency bands	ITU Web (Doc. 4/BL/25)
Recommendation ITU-R S.1592	Methodology to assess compliance of non-GSO FSS satellite systems with the additional operational limits on e _{pf} ↓ in Article S22 of the Radio Regulations	ITU Web (Doc. 4/BL/40)
Recommendation ITU-R S.1593	Methodology for frequency sharing between certain types of homogeneous non-GSO FSS systems in the 4/6 and 11/14 GHz frequency bands	ITU Web (Doc. 4/BL/41)
Recommendation ITU-R S.1595	Interference mitigation techniques to facilitate coordination between non-geostationary fixed-satellite service systems in highly elliptical orbit and non-geostationary fixed-satellite service systems in low and medium earth orbit	ITU Web (Doc. 4/BL/43)
DNR ITU-R F.[FS-BSS 2.6 GHz]	Power flux-density threshold levels between systems in the broadcasting-satellite service (sound) in the geostationary and non-geostationary satellite orbits for space-to-Earth transmissions and the fixed service in the band 2 535-2 655 MHz	Doc. 9/118
Chapter 4 - Fixed and fixed-satellite services and High Altitude Platform Systems		
Recommendation ITU-R S.524-7	Maximum permissible levels of off-axis e.i.r.p. density from earth stations in GSO network operating in the fixed-satellite service transmitting in the 6, 14 and 30 GHz frequency bands	Supplement 1 Volume 2000 Series S, Parts 1, 2 and 3
Recommendation ITU-R P.530-10	Propagation data and prediction methods required for the design of terrestrial line-of-sight systems	Supplement 1 Volume 2000 Series P
DRR ITU-R F.758-2	Considerations in the development of criteria for sharing between the terrestrial fixed service and other services	Doc. 9/BL/51
DRR ITU-R RA.769-1	Protection criteria used for radioastronomical measurements	Doc. 7/53
DRR ITU-R SA.1029-1	Interference criteria for satellite passive remote sensing	Doc. 7/50
Recommendation ITU-R F.1108-3	Determination of the criteria to protect fixed service receivers from the emissions of space stations operating in non-geostationary orbits in shared frequency bands	ITU Web (Doc. 9/BL/36)
Recommendation ITU-R F.1245-1	Mathematical model of average radiation patterns for line-of-sight point-to-point radio-relay system antennas for use in certain coordination studies and interference assessment in the frequency range from 1 to about 70 GHz	Volume 2000 Series F, Part 2
Recommendation ITU-R S.1328-4	Satellite system characteristics to be considered in frequency sharing analyses within the fixed-satellite service	ITU Web (Doc. 4/BL/36)
Recommendation ITU-R F.1336-1	Reference radiation patterns of omnidirectional, sectoral and other antennas in point-to-multipoint systems for use in sharing studies in the frequency range from 1 to about 70 GHz	Volume 2000 Series F, Part 2
Recommendation ITU-R SF.1395	Minimum propagation attenuation due to atmospheric gases for use in frequency sharing studies between the fixed-satellite service and the fixed service	Volume 2000 Series SF

Recommendation ITU-R S.1432	Apportionment of the allowable error performance degradations to fixed satellite service (FSS) hypothetical reference digital paths arising from time invariant interference for systems operating below 15 GHz	Volume 2000 Series S, Part 1
Recommendation ITU-R SF.1481-1	Frequency sharing between systems in the fixed service using high-altitude platform stations and satellite systems in the geostationary orbit in the fixed-satellite service in the bands 47.2-47.5 and 47.9-48.2 GHz	ITU Web (Doc. 4-9/BL/1)
Recommendation ITU-R SF.1484	Maximum allowable values of power flux-density at the surface of the Earth produced by non-geostationary satellites in the fixed-satellite service operating in the 37.5-42.5 GHz band to protect the fixed service	ITU Web (Doc. 4-9/BL/5)
Recommendation ITU-R F.1498-1	Deployment characteristics of fixed service systems in the band 37-40 GHz for use in sharing studies	ITU Web (Doc. 9/BL/33)
Recommendation ITU-R F.1501	Coordination distance for systems in the fixed service (FS) involving high-altitude platform stations (HAPS) sharing the frequency bands 47.2-47.5 GHz and 47.9-48.2 GHz with other systems in the fixed service	Volume 2000 Series F, Part 1A
DRR ITU-R RA.1513	Levels of data loss to radio astronomy observations and percentage-of-time criteria resulting from degradation by interference for frequency bands allocated to the radio astronomy on a primary basis	Doc. 7/51
DRR ITU-R SM.1542	The protection of passive services from unwanted emissions	ITU Web
Recommendation ITU-R S.1557	Operational requirements and characteristics of FSS systems operating in the 50/40 GHz bands for use in sharing studies between the fixed-satellite service and the fixed service	ITU Web (Doc. 4/BL/22)
Recommendation ITU-R F.1569	Technical and operational characteristics for the fixed service using high altitude platform stations in the bands 27.5-28.35 GHz and 31.0-31.3 GHz	ITU Web (Doc. 9/BL/25)
Recommendation ITU-R F.1570	Impact of uplink transmission in the fixed service using high altitude platform stations (HAPS) on the Earth exploration-satellite service (passive) in the 31.3-31.8 GHz band	ITU Web (Doc. 9/BL/26)
DNR ITU-R F.[9B/HAPS-MT]	Interference mitigation techniques for use by high altitude platform stations (HAPS) in the 27.5-28.35 GHz and 31.0-31.3 GHz bands	Doc. 9/BL/40
DNR ITU-R F.[HAPS- RAS]	Interference evaluation and operational procedure of the fixed service using High Altitude Platform Stations (HAPS) to protect the radio-astronomy service (RAS) from uplink transmission in HAPS systems in the 31.3-31.8 GHz band	Doc. 9/BL/45
DNR ITU-R F.[9B/HAPS1]	Frequency sharing between systems in the fixed service using high altitude platform stations and conventional systems in the fixed service in the bands 47.2-47.5 and 47.9-48.2 GHz	Doc. 9/BL/41
DNR ITU-R F.[HAPS- FWA]	Interference evaluation from fixed service systems using high altitude platform stations to conventional fixed service systems in the bands 27.5-28.35 and 31.0-31.3 GHz	Doc. 9/BL/42

DNR ITU-R SF. [HAPS-FSS METHOD]	A methodology for interference evaluation from the downlink of the fixed service using high altitude platform stations to the uplink of the fixed-satellite service using the geostationary satellites within the band 27.5-28.35 GHz	Doc. 4-9/BL/7
Recommendation ITU-R S.1586	Calculation of unwanted emission levels produced by a non-geostationary FSS satellite system at radio astronomy sites	ITU Web (Doc. 4/BL/30)
PDNR ITU-R SM.[BbB]	Compatibility analysis between a passive service and an active service allocated in adjacent and nearby bands	Doc. 1/1004
DNR ITU-R SF.[PFD-MULTI]	Methodology for determining power flux-density statistics for use in sharing studies between FWS and multiple FSS satellites	Doc. 4-9/BL/8
DNR ITU-R SF.[ESV-A]	The minimum distance from the coastline beyond which in-motion earth stations located on board vessels would not cause unacceptable interference to the fixed service in the bands 5 925-6 425 MHz and 14-14.5 GHz	Doc. 4/95-9/154 (Rev.1)
Recommendation ITU-R SF.1585	Example approach for determination of the composite area within which interference to fixed service stations from earth stations on board vessels when operating in motion near a coastline would need to be evaluated	ITU Web (Doc. 4-9/BL/6)
DNR ITU-R SF.[ESV-C]	Guidance for determination of interference from earth stations on vessels (ESVs) to stations in the fixed service when the ESV is within the minimum distance	Doc. 4/92-9/151 (Rev.1)
DNR ITU-R SF.[ESV-FREQ]	Use of frequencies by earth stations on board vessels transmitting in certain bands allocated to the fixed-satellite service	Doc. 4/91-9/150 (Rev.1)
Recommendation ITU-R S.1587	Provisional technical characteristics of earth stations on board vessels (ESVs) operating in the FSS networks in the frequency bands 5 925-6 425 MHz, and 14-14.5 GHz	ITU Web (Doc. 4/BL/31)
Recommendation ITU-R S.1557	Operational requirements and minimum characteristics of FSS systems operating in the 50/40 GHz bands for use in sharing studies between the fixed-satellite service and terrestrial services	ITU Web (Doc. 4/BL/22)
Recommendation ITU-R SF.1572	Methodology to evaluate the impact of space-to-Earth interference from the fixed-satellite service to the fixed service in frequency bands where precipitation is the predominant fade mechanism	ITU Web (Doc. 4-9/BL/2)
Recommendation ITU-R SF.1573	Maximum allowable values of power flux-density at the surface of the Earth by geostationary satellites in the fixed-satellite service operating in the 37.5-42.5 GHz band to protect the fixed service	ITU Web (Doc. 4-9/BL/3)
Recommendation ITU-R S.1594	Technical characteristics of high density FSS earth stations transmitting towards geostationary FSS space stations in the 30 GHz range	ITU Web (Doc. 4/BL/42)
DNR ITU-R F.[9A/NGSO3]	Interference criteria to protect fixed wireless systems from time varying aggregate interference produced by non-GSO satellites operating in other services sharing the 37-40 GHz and 40.5-42.5 GHz bands on a co-primary basis	Doc. 9/BL/39
Chapter 5 - Maritime mobile, amateur and amateur-satellite, and broadcasting services in MF and HF bands		
Recommendation ITU-R P.373-7	Definitions of maximum and minimum transmission frequencies	Volume 2000 Series P, Part 1

Recommendation ITU-R P.533-6	HF propagation prediction method	Volume 2000 Series P, Part 2
Recommendation ITU-R M.541-8	Operational procedures for the use of digital selective calling equipment in the maritime mobile service	Volume 2000 Series P, Part 3
DRR ITU-R M.585-2	Assignment and use of maritime mobile service identities	Doc. 8/75(Rev.1)
Recommendation ITU-R M.1169	Hours of service of ship stations	Volume 2000 Series P, Part 3
Recommendation ITU-R M.1170	Morse telegraphy procedures in the maritime mobile service	Volume 2000 Series P, Part 3
Recommendation ITU-R BS.1348	Service requirements for digital sound broadcasting at frequencies below 30 MHz	Volume 2000 Series BS, Part 1
Recommendation ITU-R BS.1514-1	System for digital sound broadcasting in the broadcasting bands below 30 MHz	ITU Web (Doc. 6/BL/45)
Recommendation ITU-R M.1544	Minimum qualifications of radio amateurs	ITU Web (Doc. 8/BL/1)
DNR ITU-R BS.[Doc. 6/324]	"Planning parameters" for digital sound broadcasting at frequencies below 30 MHz	Doc. 6/324 (Rev.1)
Chapter 6 - Other matters		
DRR ITU-R SM.329-9	Spurious emissions	ITU Web
DRR ITU-R RA.769-1	Protection criteria used for radioastronomical measurements	Doc. 7/53
DRR ITU-R SA.1029-1	Interference criteria for satellite passive remote sensing	Doc. 7/50
Recommendation ITU-R S.1428-1	Reference FSS earth-station radiation patterns for use in interference assessment involving non-GSO satellites in frequency bands between 10.7 GHz and 30 GHz	Volume 2000 Series S, Part 1
DRR ITU-R RA.1513	Levels of data loss to radio astronomy observations and percentage-of-time criteria resulting from degradation by interference for frequency bands allocated to the radio astronomy on a primary basis	Doc. 7/51
Recommendation ITU-R SM.1539	Variation of the boundary between the out-of-band and spurious domains required for the application of Recommendations ITU-R SM.1541 and ITU-R SM.329	Doc. 1/BL/18
Recommendation ITU-R SM.1541	Unwanted emissions in the out-of-band domain	Doc. 1/BL/19
DNR ITU-R SM.[BbB]	Compatibility analysis between a passive service and an active service allocated in adjacent and nearby bands	Doc. 1/1004
Recommendation ITU-R S.1586	Calculation of unwanted emission levels produced by a non-geostationary FSS satellite system at radio astronomy sites	ITU Web (Doc. 4/BL/30)
Recommendation ITU-R M.1583	Interference calculations between non-GSO MSS or RNSS satellite systems and radio astronomy telescope sites	ITU Web (Doc. 8/BL/16)
Chapter 7 - Future work programme		
Recommendation ITU-R V.573-4	Radiocommunication vocabulary	Volume 2000 Series V

Recommendation ITU-R F.592-3	Terminology used for radio-relay systems	Volume 2000 Series F, Part 1A
Recommendation ITU-R V.662-3	Terms and definitions	Volume 2000 Series V
Recommendation ITU-R M.1224	Vocabulary of terms for International Mobile Telecommunications-2000 (IMT-2000)	Volume 2000 Series M, Part 2
Recommendation ITU-R M.1308	Evolution of land mobile systems towards IMT-2000	Volume 2000 Series M, Part 2
Recommendation ITU-R F.1399-1	Vocabulary of terms for wireless access	Volume 2000 Series F, Part 1B
Recommendation ITU-R M.687-2	International Mobile Telecommunications-2000 (IMT-2000)	Volume 2000 Series M, Part 2
Recommendation ITU-R M.819-2	International Mobile Telecommunications-2000 (IMT-2000) for developing countries	Volume 2000 Series M, Part 2
Recommendation ITU-R M.1311	Framework for modularity and radio commonality within IMT-2000	Volume 2000 Series M, Part 2
Recommendation ITU-R M.1390	Methodology for the calculation of IMT-2000 terrestrial spectrum requirements	Volume 2000 Series M, Part 2
Recommendation ITU-R P.1411-1	Propagation data and prediction methods for the planning of short-range outdoor radiocommunication systems and radio local area networks in the frequency range 300 MHz to 100 GHz	Supplement 1 to Volume 2000 Series P, Parts 1 and 2
DRR ITU-R M.1457-1	Detailed specifications of the radio interfaces of IMT-2000	Doc. 8/BL/18
Recommendation ITU-R S.1590	Technical and operational characteristics of satellites operating in the range 20-375 THz	ITU Web (Doc. 4/BL/37)
DNR ITU-R SA.[EESS-4300]	Sharing between the Earth exploration-satellite (passive) and airborne altimeters in the aeronautical radionavigation service in the band 4 200-4 400 MHz	Doc. 7/49
DNR ITU-R P.[OPTICAL]	Propagation data required for the design of Earth-space systems operating between 20 and 375 THz	Doc. 3/74(Rev.1)
DNR ITU-R P.[THz]	Prediction methods required for the design of Earth-space systems operating between 20 and 375 THz	Doc. 3/69(Rev.1)
<p>DNR = Draft new Recommendation DRR = Draft revised Recommendation PDNR = Proposed draft new Recommendation</p>		